

Sendmail

Extension Key: **maag_sendmail**

Copyright 2004-2006, Urs Maag, <urs@maag-matzingen.ch>

This document is published under the Open Content License
available from <http://www.opencontent.org/opl.shtml>

The content of this document is related to TYPO3
- a GNU/GPL CMS/Framework available from www.typo3.com

Table of Contents

Sendmail	1	Configuration	2
Introduction	1	General.....	2
What does it do?.....	1	TypoScript Reference.....	2
Requirements.....	1	TypoScript Setup.....	2
Languages.....	1	To-Do list	3
Users manual.....	1	Changelog	3

Introduction

What does it do?

The Sendmail plugin let you send the form emails over smtp, mail, sendmail or qmail. Sending over smtp with user authentication is also available.

The plugin takes the email message and sends it with the phpmailer class version 2.0.0 rc3.

The Sendmail plugin extends the typo3 class t3lib_formmail.php.

Requirements

This extension requires TYPO3 4.1.6+ and PHP 5.0+.

Languages

Error messages from the phpmailer class takes the property \$GLOBALS['LANG']->lang for setting the error language.

Users manual

First, the extension must be installed. After the extension is installed the mails would be sent over maag_sendmail.

Configuring the plugin, see in section Configuration.

Configuration

General

TypoScript Reference

Please note that the following properties TS template setup are written in a "plugin.maag_sendmail" section.

Property:	Data type:	Description:	Default:
mailer	string / stdWrap	Type of mailer. Can be smtp, mail, sendmail, qmail	mail
mailHost	string / stdWrap	If mailer = smtp: Hostname of SMTP-Mail-Server	
port	int / stdWrap	If mailer = smtp: Port of SMTP-Mail-Server	25
smtpAuth	boolean	If mailer = smtp: Should the SMTP-Mail-Server use smtp authentication?	0
username	string / stdWrap	If mailer = smtp: Username of authentication	
password	string / stdWrap	If mailer = smtp: Password of authentication	
secure	string / stdWrap	If mailer = smtp, for secure transfers (e.g. gmail): <empty> / ssl / tls	
fromName	string / stdWrap	Name of sender. Takes this name, if no other name is defined (in formmail)	
fromName.pattern	string	Pattern for creating the from name. Define the pattern like ###name### ##prename###. Take any field name defined in the standard mail form.	
fromAddress	string / stdWrap	Email address of sender. Takes this address, if no other email address is defined (in formmail)	
replayEmail.pattern	string	Pattern for creating the replayEmail. Define the pattern like ###...###. Take any field name defined in the standard mail form.	
charSet	string / stdWrap	charSet of the email	UTF-8
redirect.success.pid	int / stdWrap	Page ID to redirect, if mail sent successfully	
redirect.failed.pid	int / stdWrap	Page ID to redirect, if mail sent unsuccessfully. If the send mail failed, there is a parameter "mailError" added to the url.	

TypoScript Setup

When installing this extension, you should use the following setting (example):

```
plugin.maag_sendmail {  
    mailer = smtp  
    mailHost = smtp.gmail.com  
    port = 465  
    smtpAuth = 1  
    username = user  
    password = pw  
    fromName = Default Sender  
    fromName.pattern = ###prename### ##name###  
    replayEmail.pattern =  
    fromAddress = Default Sender Address  
    charSet = UTF-8  
    secure = ssl  
    redirect.success.pid =  
    redirect.failed.pid =  
}
```

Example to take the error message from a failed mail sending:

```
temp.Content = COA
```

```
temp.Content {  
    10 = TEXT  
    10.data = GPvar:mailError  
    10.dataWrap = <strong>|</strong>  
}
```

To-Do list

nothing yet to do.

Changelog

Version 1.1.4:

- Updated the PHPMailer to version 5.1

Version 1.1.3:

- New Property “replayEmail.pattern” for setting the replay email with any field of the form

Version 1.1.2:

- New Property “fromName.pattern” for setting the from name with any field of the form

Version 1.1.1:

- Property to make secure transfers (for example for gmail)

Version 1.1.0:

- Initial version.